



LCD
15.1"

15.1" LCD FEATURES

The LP (Low-Profile) enclosure is a mere 1.1 inch thick and the LCD display is ¼ inch from the top of the enclosure, which means more flexibility during installation. Whether behind a wall or mounted directly on a bulkhead, LP means versatility

- Built for retrofit installation with a compact metal enclosure for increased flexibility
- No expensive switching required, three inputs included
- VGA for the Flight Display Moving Map and computer graphics
- 2 composite inputs for DVD, Glareshield camera and more
- Controls on unit or use the included IR remote to switch video source, adjust preferences, etc.
- Extremely wide viewing angle allows multiple passengers to watch same monitor
- Anti glare, scratch resistant Lexan enhances viewing experience and protects LCD
- Crystal clear LCD with industry leading brightness

Mounting Types:

Rack/Bulkhead
Ceiling
Slide
Swing
Swivel
Motorized Lift

Options:

Night Vision
Touchscreen
Bezel Keys
USB Port(s)
Quad Split Screen
Heater Glass

Available Inputs:

HD-SDI
(with pass through output)
VGA
Composite



FD151CV-LP

SPECIFICATIONS

DO-160 TESTED

FD151CV-LP Dimensions
Weight
Display Size
Display Type
Display Color
Pixel Pitch
Physical Resolution
Supported Resolution
Viewing Angle
Supported Resolution
Brightness
Case Materials

(FD151CV-LP FAA/PMA Approved)

14.14" (W) x 11.95" (H) x 1.1" (D)
5 lbs 14 oz
11.89" (W) x 8.91" (H)
15.1" TFT Color LCD
16.7 Million
0.297 mm
1024x768 (XGA)
1280 x 1024 (SXGA)
140° Horizontal/125° Vertical
1024x768 (XGA)
400 cd/m²
Aluminum

INTERFACE

Power 28VDC@1.5 Amps
PC Input VGA (High Density DB-15 Connector)
Video Input 2 Composite
Video Type Supported NTSC/PAL
Screen Control On Screen Display Menu
Remote Control IR, included

CURRENT AS OF 11/02/2009