



# WIDESCREEN LCD 26.0"

## MONITOR FEATURES

This widescreen monitor is ideal for watching movies in their true format, and is built to easily mount directly on a bulkhead

- Built for retrofit installation with a compact metal enclosure for increased flexibility
- No expensive switching required, 3 inputs included
- VGA for the Flight Display Moving Map and computer graphics
- 1 composite / 1 S-video input for DVD, Glareshield camera and more
- Button controls on unit or use included IR remote to switch video source, adjust settings, etc.
- Extremely wide viewing angle allows multiple passengers to watch same monitor
- Anti glare, scratch resistant Lexan enhances viewing experience and protects LCD
- Crystal clear LCD with industry leading brightness

## INTERFACE

Power	28V DC @ 2.2A
PC Input	VGA (Analog RGB 15 Pin D-Sub)
Video Input	S-Video, Composite Video
Video Type Supported	NTSC/PAL
Screen Control	On Screen Display Menu
Remote Control	IR, included



**FD260CV**

## SPECIFICATIONS

### DO-160 TESTED

Dimensions  
Weight  
Display Size  
Display Type  
Display Color  
Pixel Pitch  
Screen Resolution  
Brightness  
Case Materials

### FAA/PMA Approved

25.10" (W) x 15.65" (H) x 2.15" (D)  
17 lbs 6 oz  
22.7" (W) x 12.78" (H)  
26.0" TFT Color LCD  
16.7 Million  
140.5x421.5  
1366x768 (WXGA)  
400 cd/m2  
Aluminum

## 26.0" HIGH-DEFINITION LCD VERSION

### FLY HD FEATURES

HD is the best available resolution for use with the PlayStation 3 in our exclusive docking station or a Blu-Ray player. With 2 HDMI inputs, HD movies and games are now in-flight at an altitude near you

- No expensive switching required, multiple inputs included
- 2 HDMI inputs for HD sources like PlayStation 3 and Blu-Ray DVD players
- VGA for the Flight Display Moving Map and computer graphics
- 1 composite / 1 S-video input for DVD, Glareshield camera and more
- Button controls on unit or use included IR remote to switch video source, adjust settings, etc.
- RS-485 interface for integration with aircraft switching



**FD260CV Ver HD**

## SPECIFICATIONS

### DO-160 TESTED

Additional Inputs  
Protection  
External Control  
Weight  
Screen Resolution

### (FD260CV is FAA/PMA Approved)

2 HDMI (High Definition Multimedia Interface)  
HDCP Compliant  
(High bandwidth Digital Content Protection)  
RS-485  
17 lbs 6 oz  
1920x1080

CURRENT AS OF 04/20/2011

## 26.0" LCD AND MOTORIZED LIFT

### MOTORIZED LIFT FEATURES

Designed for retrofit installation in a credenza or tabletop

- Monitor can be adjusted vertically up to an inch to be flush with the top of the credenza or tabletop
- Tinnerman ball and stud receptacle on top of lift to easily attach cover plate
- Remote switch allows the monitor to be raised and lowered from any location in the aircraft
- Monitor can be manually retracted by pressing down on the top of the unit until completely stowed
- Extremely rugged motor lifts and lowers monitor smoothly over countless cycles
- Monitor and mount included



**FD260LIFT**

### SPECIFICATIONS

<b>DO-160 TESTED</b>	<b>(FD260CV is FAA/PMA approved)</b>
Dimensions Stowed	29.0" (W) x 20.75" (H) x 2.54" (D)
Dimensions Deployed	29.0" (W) x 37.90" (H) x 2.54" (D)
Weight	TBD
Power (Motor)	28VDC@ 1Amp
Switch	Double Pole, Double Throw

## 26.0" HIGH-DEFINITION LCD AND MOTORIZED LIFT

### MOTORIZED LIFT FEATURES

The same high quality lift as the FD260LIFT, with the added benefit of high-definition. HD is the best available resolution for use with the PlayStation 3 in our exclusive docking station or a Blu-Ray player. With 2 HDMI inputs, HD movies are now in-flight at an altitude near you

- No expensive switching required, multiple inputs included
- 2 HDMI inputs for HD sources like PlayStation 3 and Blu-Ray DVD players
- VGA for Flight Display Moving Map and computer graphics
- 1 composite / 1 S-video input for DVD, Glareshield camera and more
- Button controls on unit or use included IR remote to switch video source, adjust preferences, etc.
- RS-485 interface for integration with aircraft switching



**FD260LIFT Ver HD**

### SPECIFICATIONS

<b>DO-160 TESTED</b>	<b>(FD260CV is FAA/PMA approved)</b>
Additional Inputs	2 HDMI
Protection	HDCP Compliant
External Control	RS-485
Dimensions Stowed	29.0" (W) x 20.75" (H) x 2.54" (D)
Dimensions Deployed	29.0" (W) x 37.90" (H) x 2.54" (D)
Weight	TBD
Power (Motor)	28VDC@ 1Amp
Switch	Double Pole, Double Throw