



WIDESCREEN LCD 26.0"

MONITOR FEATURES

This widescreen monitor is ideal for watching movies in their true format, and is built to easily mount directly on a bulkhead

- Built for retrofit installation with a compact metal enclosure for increased flexibility
- No expensive switching required, 3 inputs included
- VGA for the Flight Display Moving Map and computer graphics
- 1 composite / 1 S-video input for DVD, Glareshield camera and more
- Button controls on unit or use included IR remote to switch video source, adjust settings, etc.
- Extremely wide viewing angle allows multiple passengers to watch same monitor
- Anti glare, scratch resistant Lexan enhances viewing experience and protects LCD
- Crystal clear LCD with industry leading brightness

INTERFACE

Power	28VDC @ 6.0 AMPS
PC Input	VGA (Analog RGB 15 Pin D-Sub)
Video Input	S-Video, Composite Video
Video Type Supported	NTSC/PAL
Screen Control	On Screen Display Menu
Remote Control	IR, included



FD260CV

SPECIFICATIONS

DO-160 TESTED

Dimensions
Weight
Display Size
Display Type
Display Color
Pixel Pitch
Screen Resolution
Brightness
Case Materials

FAA/PMA Approved

25.10" (W) x 15.65" (H) x 2.15" (D)
17 lbs 6 oz
22.7" (W) x 12.78" (H)
26.0" TFT Color LCD
16.7 Million
140.5x421.5
1366x768 (WXGA)
450 cd/m2
Aluminum

26.0" HIGH-DEFINITION LCD VERSION

FLY HD FEATURES

HD is the best available resolution for use with the PlayStation 3 in our exclusive docking station or a Blu-Ray player. With 2 HDMI inputs, HD movies and games are now in-flight at an altitude near you

- No expensive switching required, multiple inputs included
- 2 HDMI inputs for HD sources like PlayStation 3 and Blu-Ray DVD players
- VGA for the Flight Display Moving Map and computer graphics
- 1 composite / 1 S-video input for DVD, Glareshield camera and more
- Button controls on unit or use included IR remote to switch video source, adjust settings, etc.
- RS-485 interface for integration with aircraft switching



FD260CV Ver HD

SPECIFICATIONS

DO-160 TESTED

Additional Inputs
Protection
External Control
Weight

(FD260CV is FAA/PMA Approved)

2 HDMI (High Definition Multimedia Interface)
HDCP Compliant
(High bandwidth Digital Content Protection)
RS-485
18 lbs

CURRENT AS OF 01/11/2010

26.0" LCD AND MOTORIZED LIFT

MOTORIZED LIFT FEATURES

Designed for retrofit installation in a credenza or tabletop

- Monitor can be adjusted vertically up to an inch to be flush with the top of the credenza or tabletop
- Tinnerman ball and stud receptacle on top of lift to easily attach cover plate
- Remote switch allows the monitor to be raised and lowered from any location in the aircraft
- Monitor can be manually retracted by pressing down on the top of the unit until completely stowed
- Extremely rugged motor lifts and lowers monitor smoothly over countless cycles
- Monitor and mount included



FD260LIFT

SPECIFICATIONS

DO-160 TESTED	(FD260CV is FAA/PMA approved)
Dimensions Stowed	29.0" (W) x 20.75" (H) x 2.54" (D)
Dimensions Deployed	29.0" (W) x 37.90" (H) x 2.54" (D)
Weight	TBD
Power (Motor)	28VDC@ 1Amp
Switch	Double Pole, Double Throw

26.0" HIGH-DEFINITION LCD AND MOTORIZED LIFT

MOTORIZED LIFT FEATURES

The same high quality lift as the FD260LIFT, with the added benefit of high-definition. HD is the best available resolution for use with the PlayStation 3 in our exclusive docking station or a Blu-Ray player. With 2 HDMI inputs, HD movies are now in-flight at an altitude near you

- No expensive switching required, multiple inputs included
- 2 HDMI inputs for HD sources like PlayStation 3 and Blu-Ray DVD players
- VGA for Flight Display Moving Map and computer graphics
- 1 composite / 1 S-video input for DVD, Glareshield camera and more
- Button controls on unit or use included IR remote to switch video source, adjust preferences, etc.
- RS-485 interface for integration with aircraft switching



FD260LIFT Ver HD

SPECIFICATIONS

DO-160 TESTED	(FD260CV is FAA/PMA approved)
Additional Inputs	2 HDMI
Protection	HDCP Compliant
External Control	RS-485
Dimensions Stowed	29.0" (W) x 20.75" (H) x 2.54" (D)
Dimensions Deployed	29.0" (W) x 37.90" (H) x 2.54" (D)
Weight	TBD
Power (Motor)	28VDC@ 1Amp
Switch	Double Pole, Double Throw